SDMS US EPA Region V Imagery Insert Form

Document ID: 174549

	Some images in this document may be illegible or unavailable in SDMS. Please see reason(s) indicated below:
	Illegible due to bad source documents. Image(s) in SDMS is equivalent to hard copy.
LI	Specify Type of Document(s) / Comments:
X	IncludesCOLOR orXRESOLUTION variations. Unless otherwise noted, these images are available in monochrome. The source document page(s) is more legible than the images. The original document is available for viewing at the Superfund Records Center.
	Specify Type of Document(s) / Comments:
	TABLES 4, 5 & 6 - LEACHATE DISPOSAL
	Confidential Business Information (CBI). This document contains highly sensitive information. Due to confidentiality, materials with such information are not available in SDMS. You may contact the EPA Superfund Records Manager if you wish to view this document.
	Specify Type of Document(s) / Comments:
	Unscannable Material: OversizedorFormat. Due to certain scanning equipment capability limitations, the document page(s) is not available in SDMS. The original document is available for viewing at the Superfund Records center.
	Specify Type of Document(s) / Comments:
	Document is available at the EPA Region 5 Records Center.
	Specify Type of Document(s) / Comments:

Rev. 07/10/02

SUPERFUND DIVISION REMEDIAL ENFORCEMENT RESPONSE BRANCH

FIVE-YEAR REVIEW REPORT

SITE NAME: ADAMS C	DUNKY LANDFILL
	INITIAL & DATE
RPM:	3/28/03
FIVE-YEAR REVIEW COORDINATOR (Rosita Clarke):	Rell 3/27/03 4/1 coment
SECTION CHIEF:	M ha Jamah 3/28/03
JAMES N. MAYKA: WILLIAM E. MUNO:	ROW 3/27/03 up coment 3/1 to 50 mgh 3/28/03 DB. for JM 3/28/03 B for GEM 3/28/03
RETURN TO: TERRY TO	uno TREE
PHONE# 3-3236	
COMMENTS:	

(EPA:JD:02/02/99)

Five-Year Review Report

Five-Year Review Report for Adams County Landfill/Quincy Landfill Superfund Site Town of Quincy Quincy, Illinois

March 2003

PREPARED BY:

United States Environmental Protection Agency Region 5 Chicago, Illinois

3/28/03

Approved by: Date:

William E. Muno, Director Superfund Division

Table of Contents

Section		Page	
List o	f Acronyms	2	
Execu	Site Of Acronyms		
Five-	Year Review Summary Form	4	
I.	Introduction	6	
II.	Site Chronology	7	
III.	Background	8	
	Physical Characteristics	8	
	Land and Resource Use	8	
	History of Contamination	8	
Executive Five-Yell. II.	Initial Response	9	
	Basis for Taking Action	10	
IV.	Remedial Actions	11	
	Remedy Selection	11	
	System Operations/Operation and Maintenance (O&M)	13	
V.	Progress Since the Last Five-Year Review	18	
VI.	Five - Year Review Process	18	
	Administrative Components	18	
	Community Involvement	18	
	Document Review	18	
	Data Review	19	
	Site Inspections	23	
	Interviews	24	
VII.	Technical Assessment	24	
	Question A: Is the remedy functioning as intended by the decision documents?	24	
	Question C: Has any other information come to light that could call into question the protectiveness	,23	
	of the remedy?	26	
	Technical Assessment Summary	26	

VIII.	Issues	26
IX.	Recommendations and Follow-up Actions	28
х.	Protectiveness Statement(s)	29
XI.	Next Review	29
Tables		
	Table 1 - Chronology of Site Events	7
	Table 2 - Budget Summary	15
	Table 3 - O&M Costs	16
	Table 4 - Leachate Disposal	16
	Table 5 - Leachate Disposal	17
	Table 6 - Leachate Disposal.	17
	Table 7 - 1997-1998 Groundwater Samples for Arsenic	22
	Table 8 - 1997-1998 Groundwater Samples for Methacrylonitrile	22
	Table 9 - 1997-1998 Groundwater Samples for Vinyl Chloride	23
	Table 10 - Issues	27
	Table 11 - Recommendations and Follow-Up Actions	28
	*	

Attachments

Attachment 1 - Site Location Map

Attachment 2 - List of Documents Reviewed

Attachment 3 - Interview Report

Attachment 4 - Summary of Groundwater Chemical Data from 1997-2000

List of Acronyms

ARAR Applicable or Relevant and Appropriate Requirement

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPA United States Environmental Protection Agency

CFR Code of Federal Regulations

ESD Explanation of Significant Difference

MCI, Maximum Contaminant Level

MCEG Maximum Contaminant Level Goal

NCP National Contingency Plan

NPL National Priorities List

O&M Operation and Maintenance

PAH Polyaromatic Hydrocarbon

PCB Polychlorinated Biphenyl

PPB Parts per Billion

PRP Potentially Responsible Party

RA Remedial Action

RAO Remedial Action Objective

RD Remedial Design

RI/FS Remedial Investigation/Feasibility Study

ROD Record of Decision

VOC Volatile Organic Compound

Illinois EPA Illinois Environmental Protection Agency

Executive Summary

The five-year review of the Adams County Landfill/Quincy Landfill site in Quincy, Illinois was completed in March 2003. The remedy is protective of human health and the environment in the short term. There are no current exposure pathways and the remedy appears to be functioning as designed. The cover and putting citizens on public water supply eliminates the source of contamination and have achieved the remedial objectives to minimize the migration of contaminants to groundwater and surface water and prevent direct contact with, or ingestion of, contaminants in soils and sediments. A few deficiencies that do not immediately impact the protectiveness of the remedy were noted.

Both the Health and Safety Plan and the Contingency Plans are in place, sufficient to control risks, and properly implemented. The remedy for the Adams/Quincy County Landfill (Adams County Landfill) Superfund Site (the site) include landfill cover/containment, access controls, institutional controls and leachate collection system.

The Illinois Environmental Protection Agency (Illinois EPA) in cooperation with the United States Environmental Protection Agency (U.S. EPA) completed oversight of all major construction activities for the Adams County Quincy Landfills 2 & 3 Superfund Site (site).

The site is located along Old Broadway Road south of Illinois Route 104 approximately five miles east of the City of Quincy within the eastern $^{1}/_{2}$ of Section 1, Township 2 South, Range 8 West of the Third Principal Meridian in Melrose Township, Adams County, Illinois. The total size of the site is fifty-six acres with the landfill disposal activities occurring in an area of about 33 acres north of the intermittent stream which approximately bisects the site in an east to west fashion. The northern limit of the facility is Old Broadway Road, the western boundary is a private gravel road, the southern boundary is a wooded tract, the eastern side of the Site is bounded by pasture land and a home site.

The site achieved construction completion in March 1999. The assessment of this five-year review found that the remedy was constructed in accordance with the requirements of the September 30, 1993, Record of Decision (ROD). The remedy is protective of human health and the environment in the short term and there are no current exposure pathways and the remedy appears to be functioning as designed. The landfill cap has been constructed over all the wastes, a leachate collection system is operating, and a public water supply was provided to the residents.

Five-Year Review Summary Form

SITE IDENTIFICATION							
Site name (from WasteLAN): AdamsCounty Landfill/Quincy Landfill							
EPA ID (from WasteLAN): ILD980607055							
Region: V	State: L		City/County: Quincy/Adams				
	SITE S	TATUS					
NPL status: x Final Deleted other (spec	ify)						
Remediation status (choose all that apply):	Under Construction X	Operating Complete					
Multiple OUs? Yes x No	Construction comple	tion date: 3-31-1999					
Has site been put into reuse? YES x NC)						
	REVIEW	STATUS					
Reviewing agency: x EPA X State Tribe	Other Federal Agency						
Author name: Terry Roundtree							
Author title: Remedial Project Manager Author affiliation: EPA Region V							
Review period: 10/1/2002 to 3/30/2003							
Date(s) of site inspection: 12/15/2002							
Type of review: X Statutory Policy Post-SARA Pre-Sara NPL-Removal only Non-NPL Remedial Action Site NPL State/Tribe-lead (Regional Discretion)							
Review number: X 1(first) 2 (second) 3	(third) Other (specify)						
Triggering action X Actual RA Onsite Construction at OU # Actual RA Start at OU# Construction Completion Previous Five-Year Review Report Other (specify)							
Triggering action date (from WasteLAN): 3	3/10/1998						
Due date (five years after triggering action	date): 3/30/2003						

Five-Year Review Summary Form, cont'd.

Issue:

- 1) Damage to Landfill cover has occurred in the past due to heavy equipment and animals.
- 2) Leachate spills have occurred in the past.

Recommendations and Follow-up Actions:

- 1) Continue monitoring landfill cover and make repairs to the cover as needed.
- 2) Need for continual O&M leachate system

Protectiveness Statement(s):

The remedy is protective of human health and the environment in the short term. There are no current exposure pathways and the remedy appears to be functioning as designed. The cover and putting citizens on public water supply eliminates the source of contamination and have achieved the remedial objectives to minimize the migration of contaminants to groundwater and surface water and prevent direct contact with, or ingestion of, contaminants in soils and sediments.

Long-term protectiveness of the of the remedial action will be achieved when cleanup goals are met.

Other Comments:

There have been two repairs on the cap since the construction of the remedial action. The tears in the cap were due to heavy equipment coming in contact with the cap. The cap has been repaired and will be evaluated further in the summer of 2003 for further damage. There are some concerns with the leachate run off at the site probably due to the tear in the cap. A full system evaluation is scheduled in the summer of 2003.

ADAMS COUNTY LANDFILL/QUINCY LANDFILL SITE QUINCY, ILLINOIS FIVE YEAR REVIEW REPORT

I. INTRODUCTION

The purpose of the five-year review is to determine whether the remedy at a site is protective of human health and the environment. The methods, findings, and conclusions of reviews are documented in Five-Year Review reports. In addition, Five-Year Review reports identify issues found during the review, if any, and identify recommendations to address them.

EPA is preparing this Five-Year Review report pursuant to CERCLA §121 and the National Contingency Plan (NCP). CERCLA §121 states:

If the President selects a remedial action that results in any hazardous substances, pollutants, or contaminants remaining at the site, the President shall review such remedial action no less often than each five years after the initiation of such remedial action to assure that human health and the environment are being protected by the remedial action being implemented In addition, if upon such review it is the judgement of the President that action is appropriate at such site in accordance with section [104] or [106], the President shall take or require such action. The President shall report to the Congress a list of facilities for which such review is required, the results of all such reviews, and any actions taken as a result of such reviews.

EPA interpreted this requirement further in the NCP; 40 CFR §300.430(f)(4)(ii) states:

If a remedial action is selected that results in hazardous substances, pollutants, or contaminants remaining at the site above levels that allow for unlimited use and unrestricted exposure, the lead agency shall review such action no less often than every five years after the initiation of the selected remedial action.

EPA, Region 5, is conducting this first five-year review of the remedy implemented at the Adams County Landfill Superfund Site in Quincy, Illinois. This review was conducted by the Remedial Project Manager (RPM) for the entire site from May through December 2002. This report documents the results of the review.

The triggering action for this statutory review is the initiation of construction activities for the remedial action on March 10, 1998. The five-year review is required due to the fact that hazardous substances, pollutants, or contaminants remain at the site that allow for unlimited use and unrestricted exposure.

II. SITE CHRONOLOGY

Table 1 - Chronology of Site Events

EVENT	DATE
Initial Discovery of Problem	May 1, 1981
Proposed on NPL	June 24, 1988
Listed on NPL	August 30, 1990
RI/FS (entire site)	September 12, 1990 -September 30, 1993
ROD (entire site)	September 30, 1993
RD	March 31, 1996 – December 18, 1997
ESD	December 1997
RA Start	December 18, 1997
RA Construction Start	March 10, 1998
RA Completed	March 31, 1999
Final Inspection of Entire Site	March 24 1999
PCOR	March 31, 1999,
O&M Activities Began	August 1, 1999
First Five - Year Review	March 2003
Next Five - Year Review	March 2008

III. BACKGROUND

Physical Characteristics

The Adams County Quincy Landfills 2 & 3 site is located in a rural area on Old Broadway Road south of Illinois Route 104 approximately 5 miles east of the City of Quincy within the eastern 1/2 of Section 1, Township 2 South, Range 8 West in Melrose Township, Adams County in west-central Illinois. The site's northern limits are bounded by Old Broadway Road, the eastern boundary is adjacent to pastureland, the southern limit is bounded by a wooded tract, and the western boundary is bordered by a private lane.

The fifty-six-acre site is wire fenced on all sides with a locked access gate on the northern boundary. The only structure on site is a metal storage building located near the north entrance gate. The remnants of an un-maintained gravel roadway cross the middle of the site from the entrance gate on the north to the southwestern side of the site.

The landfill is located on an upland of the Mississippi River and the topography of the area is generally hilly, sloping from the north to the south and southwest. Surface drainage on the site flows to the south and southwest to an unnamed stream tributary to Mill Creek. A drainage ditch on the western boundary of the site collects surface runoff and discharges to the stream. A map of the site is provided in attachment 1.

Land and Resource Use

Prior to Initiation of landfill operations in 1967, the Site was used for the pasturage of livestock. In January 1967 the Adams County Health Department approved a landfill development permit requested by Ronald Thomas. In March 1971, the Illinois EPA issued Ronald Thomas and Marion Neill a permit to operate a landfill at the Site. Marion Neill's association with the landfill ceased in October 1971. The Illinois EPA issued Ronald and Sarah Thomas a permit to operate the landfill in February 1972. The City of Quincy leased the landfill from Ronald Thomas in September 1972, and in January 1973 the Illinois EPA issued a permit to the City of Quincy to operate the landfill. Permits to expand the size of the landfill were issued to the City of Quincy by the Illinois EPA in 1974 and in 1975. The City operated the Site until August 1978 and purchased the Site from Ronald and Sarah Thomas in April 1982.

History of Contamination

Under operation by the City of Quincy, the landfill was alleged to have received liquid wastes which were reportedly retained in holding pits located on the north and west portions of the Site near completed landfill trenches. Liquid wastes were reportedly pumped into the completed trenches by well paint injectors and covered with fill. After the closure of Quincy Municipal Landfill #1 in September 1972 the Site became the only operating landfill in Adams County until August of 1975. During its operational history the Site received the majority of the solid waste generated in the county, as well as industrial waste from the City of Quincy's manufacturing

sector. Liquid industrial wastes including solvents, acids, sludges, spent non-halogenated solvents, spent halogenated solvents used in degreasing, wastewater treatment sludges from electroplating operations, hydraulic oil, machine coolants, thinners, paint solvents, methylchloroethene, selenium, toluene, methylene chloride, acetone, and chloroethene were allegedly landfilled at the Site. No leachate collection or containment system was ever installed on the Site. Numerous leachate seeps occur throughout the landfill. Most seeps are located on the southwestern side of the Site, although several have been seen in the old roadway and a large seepage area occurs in a low-lying area in the middle of the Site. Leachate collects in low areas and is potential for off-site surface migration, primarily in two locations-along the western boundary fence and on the southwest to the nearby stream.

Initial Response

A preliminary assessment was completed in July 1983 by the EPA Field Investigation Team (FIT). The site received a Hazard Ranking Score (HRS) score above 28.5 and was placed on the National Priorities List (NPL) on August 30, 1990.

On May 19, 1981 the City of Quincy completed a Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Notification of Hazardous Waste Site form for the Adams County Quincy Landfills 2 & 3 site. The notification acknowledged the landfill disposal of unknown quantities of inorganics, solvents, heavy metals, mixed municipal wastes, and unknown wastes. Additional notices were received from generators of wastes disposed at the site.

On July 1, 1983, a preliminary assessment of the site was completed by Ecology and Environment, Inc., a field investigative team contractor for the United States Environmental Protection Agency (U.S. EPA). The preliminary assessment estimated that approximately 3000 people were potentially affected by groundwater contamination from spent halogenated solvents used in degreasing, wastewater treatment sludge from electroplating operations, and 1,1,1-trichloroethane accepted at the site.

On March 7, 1984, the same U.S. EPA contractor completed a site inspection. It was estimated that the site had received 343,000 gallons of sludge containing paint and toluene; 2,800,000 gallons of oily waste; 312,000 gallons of solvents; 343,200 gallons of other organic chemicals; 180,000 gallons of inorganic chemicals; 180,000 gallons of bases. Estimates were based on Illinois EPA supplemental permits for disposal at the site.

Basis for Taking Action

Contaminants

Hazardous substances that have been released at the site in each media include:

Soil
Benzene
Ethylbenzene
Total Xylenes

Bis (2 -ethylhexyl phthalate)

Chloroethane

Lead Mercury Arsenic Selenium

1,1-Dichloroethane
Trans-1,2-dichloroethene
Tetrachloroethene
1,1,1-Trichloroethane
Vinyl Chloride
1,1-dichloroethene
Arochlor-1254 (PCB)
Di-nButylphthalate

Leachate

Benzene Ethylbenzene Total Xylenes

Bis (2 -ethylhexyl phthalate)

Chloroethane

Lead Mercury Arsenic Selenium

1,1-Dichloroethane
Trans-1,2-dichloroethene
Tetrachloroethene
1,1,1-Trichloroethane
Vinyl Chloride
1,1-dichloroethene
Arochlor-1254 (PCB)
Arochlor-1242 (PCB)
Chlorobenzene

Groundwater

Benzene Ethylbenzene Total Xylenes

Bis (2 -ethylhexyl phthalate)

Chloroethane

Lead Mercury Arsenic Selenium

1,1-Dichloroethane Trichloroethee

Trans-1,2-dichloroethene

Tetrachloroethene 1,1,1 -Trichloroethane

Vinyl Chloride 1,1-dichloroethene Exposure to soil and groundwater is associated with significant human health risks due to exceedances of EPA's risk management criteria for the reasonable maximum exposure scenarios. The carcinogenic risks were highest for exposure to contaminated groundwater from a possible future ingestion pathway. Soil contaminants posed the greatest non-carcinogenic risk to human health through dermal contact and ingestion by children and future workers, primarily from lead and arsenic.

IV. REMEDIAL ACTIONS

Remedy Selection

The record of decision (ROD) for the Adams/Quincy County Landfill site was signed on September 29, 1993. The remedial action objective addresses two areas of concern, leachate and groundwater. The leachate remedial action addresses the source of the contamination by collecting and treating on-site waste. The function of this action is to control the landfill site as a source of groundwater contamination, to reduce the risks associated with the site and reduce exposure to contaminated materials, and to prevent untreated leachate from running off site. The groundwater response action involves long-term monitoring with cleanup levels. Failure to meet those cleanup levels will trigger further remedial action.

The major components of the selected remedy include:

- · Installation of a security fence around the landfill site;
- · Deed restrictions to prohibit groundwater use and building construction on the site;
- · Leachate collection, treatment, and monitoring;
- · Installation of surface controls to reduce erosion;
- · Landfill cap improvements to provide a minimum three feet of cover on the landfill;
- · Provision of a public water supply to nearby residents;
- · Groundwater monitoring;
- · Groundwater containment and treatment if groundwater cleanup levels are not met and maintained.

Explanation of Significant Differences

In December 1997, the Illinois EPA issued an explanation of significant differences (ESD) which modified the remedy selected in the ROD. The ESD modified two parts of the selected remedy; warning sign language and leachate discharge to the Publicly Owned Treatment Works (POTW) rather than to surface waters by way of a NPDES permit. Both modifications to the remedy were considered minor and the leachate discharge to a POTW was originally evaluated in the Focused Feasibility Study and the ROD and were available to the public for comment, consequently this change did not necessitate public involvement and an ESD was signed by the Illinois EPA with concurrence from the U.S. EPA.

Remedy Implementation

The remedy includes physical access restriction with a six-foot high cyclone fence with barbed wire at the top, around the entire site sufficient to prevent the public from easily entering the site. The fence is posted with numerous visible warning signs to inform the public of potential site hazards.

The site's real estate deed include prohibition of on-site groundwater use; on-site building construction; and on-site drilling except for the purposes of remedial design, sampling, monitoring, and remedial action.

A public water supply was supplied to six nearby residences located northwest of the site in order to eliminate the groundwater exposure pathway to those persons consuming groundwater.

The remedy includes a groundwater monitoring program to track the changes in impact of site constituents on groundwater, which would then be used to determine if additional actions are triggered by concentrations exceeding levels pursuant to the Illinois Groundwater Quality Standards at 35 Illinois Administrative Code 620. It should be noted that a contaminated groundwater plume migrating off site has not been scientifically identified and located. However, no other source of off-site groundwater contamination has been identified.

This Record of Decision did not require the immediate implementation of an active groundwater remedy because existing data indicate that relatively few sampling results showed groundwater contamination at levels of concern. The leachate source control remedy has a positive impact on groundwater quality, and effective source control combined with natural attenuation which adequately address low-level groundwater contamination. Groundwater monitoring indicates that contamination has not exceeded compliance levels, a groundwater pump and treat system will be installed to minimize contaminant migration if levels are exceeded.

The monitoring program is consistent with 35 Illinois Administrative Code 620.505 and 620.510. A groundwater management zone as described at 35 Illinois Administrative Code 620 must be established for areas undergoing effective corrective action.

Monitoring would continue for a minimum of five years with duration of monitoring dependent on results of the statistical evaluation of groundwater data. Monitoring may cease after standards at 35 Illinois Administrative Code 620.410 have been complied with for a minimum of one year.

Pursuant to the requirements of 35 Illinois Administrative Code 724.195 a groundwater point of compliance must be established at the site boundary, which is also the source boundary. Compliance shall be determined by analysis for the parameters in Appendix I at 35 Illinois Administrative Code 724.

The leachate monitoring program tests leachate for five-day biochemical oxygen demand, chemical oxygen demand, total suspended solids, dissolved iron, pH, and any other parameters known present based on analytical data or believed present at the point of leachate discharge into

surface waters. Any discharge to surface waters of the State is subject to the NPDES program at 40 CFR 122, which is implemented in Illinois pursuant to 35 Illinois Administrative Code 309.

Surface controls including berms, lined ditches, and catch basins manage surface water infiltration into the landfill and to minimize landfill surface erosion. The purpose of the controls is to direct infiltration away from known disposal areas.

Components of the remedy were constructed and maintained pursuant to the requirements of 35 Illinois Administrative Code 807 and 811, Solid and Special Waste Management Regulations, specifically regarding final cover and closure requirements. This includes a minimum of three feet of clay cover over the landfill surface, particularly in areas of cap erosion and leachate management. Site leachate is collected through a network of subsurface drains and is discharged to the City of Quincy Wastewater Treatment Plant for treatment.

The site achieved construction completion in March 1999. A Preliminary Close Out Report (PCOR) was completed on March 31, 1999.

System Operations/Operation and Maintenance (O&M)

Leachate treatment is provided by the City of Quincy Wastewater Treatment Plant. In June of 1998, over two thousand feet of leachate collection lines were installed in a trench/french drain type manner at depths ranging from three to ten feet along the shallow down gradient (south and west) sides of the site. A collection tank was installed to store the collected leachate. In the fall of 1998, the construction of the solid waste cap was completed over the thirty acres of landfill. The cap consists of a geo-synthetic clay liner, a gravel drainage layer, and a protective/vegetative layer. Landfill gas is released via a network of passive vents installed through the cap in late 1998.

The implementation of the remedial action commenced on March 10, 1998, the main components of the selected remedy include: Installation of a security fence around the landfill site; deed restrictions to prohibit groundwater use and building construction on the site; leachate collection, treatment, and monitoring; installation of surface controls to reduce erosion; landfill cap and provision of a public water supply to nearby residents; final site grading, fence repairs, erosion controls, well repairs, final seeding, and minor access road repair work and construction were completed in September 1999.

Operation, maintenance, and monitoring activities are performed by Conestoga-Rovers & Associates (CRA) a contractor for the PRP Group. In addition, the City of Quincy has on site personnel performing activities associated with operation and maintenance.

Maintenance activities for the final cover include mowing, earthwork activities to correct erosion and sedimentation problems, re-vegetation of disturbed or distressed areas in accordance with RD specifications, regrading in settlement areas as determined necessary, and localized repairs due to intrusion, vandalism, etc. The final cover is inspected quarterly for signs of damage. In

any event, inspections are projected to continue for a minimum period of 30 years (see Tables 2-6 for O&M costs and leachate disposal volumes).

Storm water management system maintenance involves activities to maintain the flow of storm water through the channels, drop basins, discharge structures, etc. which comprise the system. O&M activities require that the integrity of the stream bank is stabilized. These activities include: the clearing of debris to allow for water flow, the re-vegetation of vegetated channels and berms were necessary, earthwork necessary to maintain channel slopes and channel berms.

Operation of the leachate management system involves the periodic removal of collected leachate from the storage tank with subsequent transportation to and disposal at an offsite treatment facility, currently the City of Quincy Publicly Owned Treatment Works. The leachate storage tank has a capacity of 10,000 gallons which is approximately 3 times the maximum anticipated a 5-day leachate generation rate for the facility. The frequency of leachate removal, transport, and disposal activities is dependent on the results of ongoing monitoring activities performed to gage leachate generation and collection quantities. Leachate is removed from the leachate storage tank via a vacuum truck or portable pump to a tanker truck. The leachate is then transported to the City of Quincy POTW for disposal.

Maintenance of the leachate management system requires activities necessary to ensure the system performs as designed. The system has been designed to collect leachate from known leachate seep locations and direct the leachate through the collection and conveyance piping, via gravity flow, to the leachate storage tank for eventual removal, treatment, transport, and disposal. Maintenance activities include the cleaning of piping runs to remove blockages and solids buildup and the repair/replacement of system appurtenances (manhole covers, tank vents, access covers, valves, clean out ports, etc.) as required.

Inspection of monitoring wells is performed to evaluate well conditions, whenever a sampling round is undertaken. The inspection involves looking at general well conditions including the condition of the lock, cap, protective casing, pad (if present), well casing, etc.

Table 2 : Budget Summary

CY 2002

BUDGET SUMMARY

POST-CLOSURE ACTIVITIES

ADAMS COUNTY QUINCY LANDFILLS NO.2 & 3

QUINCY, ILLINOIS

Task	Current CRA Subcodes	Budget Estimate	Total Cost To Date ⁴	Budget Remaining
Project Management	11	\$ 15,000.00	\$ 3,732.40	11,267.60
Support to City of Quincy for				TDD
Miscellaneous Issues	12	\$ 7,000.00	\$ 1,744.73	TBD
Operation and Maintenance Plan ¹	13	\$ 3,500.00	\$ 0.00	\$3,500.00
Meetings with Group and IEPA	15	\$ 7,000.00	\$0.00	TBD
Post Closure Groundwater Monitoring,				
Off-site Gas Migration Investigation,				
Downgradient Groundwater Investigation	17	\$144,700.00	\$ 0.00	\$ 144,700.00
Additional Illinois EPA Issues Related to				
Post Closure and Future Operation and				
Maintenance	18	TBD	\$ 0.00	TBD
TOTAL - BUDGETED TASKS:		\$ 177,200.00	\$ 5,477.13	TBD

Table 3- Annual System Operations/O&M Costs

Date	Total O&M Costs	
From	То	Total Oak Costs
August 1999	August 2000	\$154,194
August 2000	August 2001	\$201,153
August 2001	August 2002	\$123,923
August 2002	August 2003	\$33,424

Table 4: Leachate Disposal




Table 5: Leachate Disposal





Table 6: Leachate Disposal



V. PROGRESS SINCE THE LAST FIVE-YEAR REVIEW

This is the first five-year review for the Adams/Quincy Landfill Site.

VI. FIVE-YEAR REVIEW PROCESS

Administrative Components

Members of the Illinois EPA and the City of Quincy were notified of the initiation of the five-year review in August 2002. The Adams/Quincy Landfill Five-Year Review team was led by Terry Roundtree of EPA, RPM for the site, and included the Illinois EPA (Rick Lanham, Project Manager), Phil Harvey of Conestoga-Rovers & Associates (CRA) contractor for the City of Quincy, Donald Kulek and Charles Jones representatives of the City of Quincy.

This five-year review consisted of the following activities: a review of relevant documents (see Attachment 2); interviews with local government officials and representatives of the construction and the operations contractors; and a site inspection. In addition, a notice regarding the forthcoming review was placed in the local newspaper. The completed report will be placed in the information repository. Notice of its completion will be placed in the local newspaper.

Community Involvement

Activities to involve the community in the five-year review process were initiated in November 13, 2002, with a notification to the local newspaper for the Adams County/Quincy Landfill Superfund site stating that a five-year review is being conducted at the site. The add announced the start of the five-year review and invited citizens to get involved in the process.

Since the November 13, 2002, notice, there has been no member of the community that has voiced any interest or opinion concerning the five-year review process.

Document Review

This five-year review consisted of a review of relevant documents including O&M records, evaluation reports, monitoring data and Interview Report (See Attachment 3). Applicable groundwater cleanup standards, as listed in the 1993 ROD, were reviewed.

Data Review

The Post-Closure Groundwater Sampling Plan was submitted by the PRPs in late April 2001. Also, a Field Sampling and Analysis Plan for off-site Groundwater sampling was submitted at that time. After considerable review and discussions with the PRPs, the Illinois EPA accepted the plans in early April 2002. However, the Illinois EPA's requirement for additional off-site groundwater investigation and monitoring well installation/sampling did not start until early March 2003 due to the PRPs difficulties in negotiating access agreements. The additional investigation and groundwater monitoring/sampling will follow the April 2001 protocol.

Prior to the start of the remedial action, nineteen Site groundwater monitoring wells were sampled in the early June (spring) and late September (fall) of 1997, and again in the January (winter) of 1998. These wells were sampled for metals, volatile organic compounds (VOCs), and semi-volatile organic compounds (SVOCs). Four of the nineteen wells around the perimeter of the site were also sampled for herbicides, pesticides, and polychlorinated biphenyls (PCBs).

The Illinois Department of Public Health (IDPH) evaluated the results of the 1990 groundwater summary data and the 1997 on-site groundwater samples provided by the Illinois EPA. Certain groundwater samples exceeded the comparison values for arsenic (Table 7). Again, wells with the highest levels of arsenic were in the areas of leachate seeps or surface runoff on the site.

The levels of two VOCs, methacrylonitrile and vinyl chloride, exceeded comparison values or MCLs in on-site groundwater samples (Tables 8 and 9). IDPH also reviewed on-site groundwater monitoring and residential well summary statistics provided by the Illinois EPA. The frequency of detection for vinyl chloride was 4 in 60. Two of these detections were from one monitoring well, and two were from residential wells. The homes using these wells were connected to public water in 1986, but Illinois EPA kept the wells open for further sampling. These private wells were sealed in 1998. With the provision for municipal water, there are no known groundwater receptors adjacent to, or down gradient from, the landfill. All adjacent residents are on municipal water.

The most recent sampling of Site groundwater occurred in November 2000 (Attachment 4), additional sampling was postponed due to disagreement with the PRPs over the requirements of the Remedial Design/Remedial Action (RD/RA) Consent Decree and Statement of Work. Those issues were resolved in April 2002 with the requirement that further off-site monitoring and sampling was necessary and that access agreements were required for this and a related landfill gas investigation. The November 2000 sampling event report was submitted by the PRPs

consultant to the Illinois EPA in February 2001. The first post-closure sampling event was intended to confirm the previous data (Tables 7-9), or determine if changes in the distribution of landfill constituents/contaminants have occurred since the completion of the landfill cap and leachate collection system. The first post-closure monitoring event was performed using the same procedures, sample locations, and analytical parameters as the previous 1997-98 sampling rounds.

The concentrations of the detected chemicals in the November 2000 sampling event (Attachment 4) are, in general, similar to previous sampling events in Tables 7-9. Important exceptions are that neither arsenic nor lead were detected in any wells in the November samples. Both arsenic and lead had been detected in samples from several monitoring wells in previous events (1997-1998).

Exceedences occurred only in shallow monitoring wells. The shallow wells are completed for the most part in glacial till underlying and adjacent to the waste. Most metal exceedences of the standards are for iron and manganese concentrations. It is possible that this maybe naturally occurring, as the distribution of iron and manganese detections is uniform throughout the Site, and because both metals are common constituents within the dolomite source rock. The only other metal exceedences are barium and nickel which occurred in one sample from monitoring well 2D. None of the metals results for the deep wells exceeded the standards.

VOCs that exceeded the standards are benzene and well 2D and vinyl chloride at 4D and Q3D. Other organic compounds that were commonly detected in samples from shallow wells include 1,1-dichloroethane, chloroethane, cis-1,2-dichloroethene, trichloroethene, and toluene. These COCs were all detected at concentrations below the standards.

Conclusion

The data collected from the November 2000 sampling event is consistent with the data from the previous four events, or those prior to cap and leachate collection completion. The groundwater data indicate that the shallow till, and more importantly, the bedrock groundwater beneath the sate, is. not significantly affected by landfill contaminants VOCs concentrations are low and the two compounds that exceed the standards, benzene and vinyl chloride, typically degrade readily. Additionally, these were only detected in shallow wells adjacent to waste limits. The detected compounds are typical of older municipal landfills, since these types of waste are known to contain hazardous substances that can leach to groundwater.

The frequency of metal detections is low, as are the exceedences of the standards. Where exceedences occur, the concentrations are generally just above the standard. Most of the metal exceedences are for iron and manganese which may be naturally occurring. There is no health based federal MCL for iron or manganese in drinking water. The few exceedences were found to occur in samples collected from shallow wells directly adjacent to the waste. Drinking wells within the Quincy's area utilize the deeper bedrock aquifers, therefore, groundwater within the bedrock/channel sand aquifer is the primary concern in regard to off-site migration. However, it should be noted that there are no private, or public, water wells currently in use within a radius of 0.75 miles from the landfill. As such, the November 2000 sampling event demonstrated that no exceedences occur in the bedrock/channel sand groundwater migrating off Site to the west and northwest of the site.

Leachate

A leachate collection system was installed at the site during the summer of 1998. Conveyance piping was installed around the east, west, and south perimeters of the site. Collected leachate is disposed at the Quincy Wastewater Treatment Facility. Leachate samples collected in June and July 1998 by the Illinois Department of Public Health contained elevated levels of vinyl chloride. Although these samples were collected without Illinois EPA oversight and laboratory errors were reported, the results reflected previous leachate sampling done by the Illinois EPA. Information dated to 1986 from the RI, indicated the leachate is characteristically non-hazardous and could be managed by City of Quincy Wastewater Treatment Facility. The results of the analysis presented in Spring 1997, Groundwater/Leachate Monitoring Report indicated similar findings. The design of the leachate management/collection system, based on the data available at that time, required compatibility of the collection system with the leachate and final deposition of the leachate. In October 2000, the leachate holding tank liquids and sludge were cleaned out and sampled. The sample results indicated that the vast majority of the chemicals sampled for were below detection limits. All waste within limits was allowed by the Quincy Wastewater Treatment Facility permit for disposal.

Table 7. 1997-1998 On-site Groundwater Quarterly Samples for Arsenic [4]

(Comparison values for arsenic – EMEG: child 3 ppb, adult 10 ppb; CREG: 0.02 ppb MCL: 50 ppb)¹

Well	Spring (ppb)	Summer (ppb)	Fall (ppb)	Winter (ppb)	Depth (feet)
Q2D	<1	<1	4	<1	86.8'
Q3D	5	<1	3	<1	46'
Q4D	5	4	3	1	87.9'
Q4S	<1	<1	3	<1	33'
2D	110	100	89	70	18'
3D	<1	2	4	4	26.5'
4D	3	<1	3	4	33'

¹EMEG – environmental dose media evaluation guide; CREG – cancer risk evaluation guide

 $MCL-maximum\ contaminant\ level$

ppb = parts per billion

Bold results indicate monitoring wells in areas of leachate runoff.

Table 8. 1997-1998 On-site Groundwater Quarterly Samples for Methacrylonitrile [4]

(Comparison values for methacrylonitrile – REMG: child 1 ppb, adult 4 ppb)¹

Well	Spring (ppb)	Summer (ppb)	Fall (ppb)	Winter (ppb)	Depth (feet)
Q6S	<5	<10	43	<10	141.94'
2D	<5	<10	59	<10	18'

¹RMEG – reference dose media evaluation guide

ppb = parts per billion

Bold results indicate monitoring wells in areas of leachate runoff.

Table 9. 1997-1998 On-site Groundwater Quarterly Samples for Vinyl Chloride [4]

(Comparison values for vinyl chloride – EMEG: child 0.2 ppb, adult 0.7 ppb; MCL: 2 ppb)¹

Well	Spring (ppb)	Summer (ppb)	Fall (ppb)	Winter (ppb)	Depth (feet)
Q3D	4.9 est.	4.3 est.	2.8 est.	4.2 est.	46'
2D	<10	<10	<10	1.2 est.	18'
4D	3.5 est.	<10	2.3 est.	2.6 est.	33'

¹EMEG – environmental dose media evaluation guide; MCL – maximum contaminant level

ppb = parts per billion

est. - result represents estimated value that is below the Practical Quantitative Limit.

Bold results indicate monitoring wells in areas of leachate runoff.

Site Inspections

Site inspections took place in June 2002, September 2002 and December 2002. During the site inspections, the landfill cover was inspected and leachate collection system was observed. The inspection evaluated the landfill cap, the leachate treatment system, the surface water drainage system, and site fencing. Conditions during the inspections were favorable with mild temperatures and no precipitation. The site vegetation was in good condition.

The landfill cap was found to be in good condition. The vegetative cover was adequate and continuing to improve or mature, with no distressed areas, trees or shrubs. No noticeable depressions, excessive cracks, leachate seeps, odors, or other indications of distress were noted. No significant ponding has been observed on the cap. There was some evidence of several small rodent burrows on the south side of the cap. The burrows were generally less than 12 inches deep and no geosynthetics were damaged or waste exposed. Once burrows are identified, they are backfilled with equivalent cap material and, if necessary, repellants are used to discourage further rodent activity.

The fifty-six-acre site is wire fenced on all sides with a locked access gate on the northern boundary. The wire fence is in disrepair in some areas, particularly the western boundary, and allows easy access to anyone wishing to walk on site. The City of Quincy is repairing the fence and posting more signs to warn people that no trespassing is allowed. However, since the site is not continuously staffed, it occasionally gets trespassers. The City of Quincy is also making

periodic checks for trespassers. The City repairs the ruts when they exceed a few inches in depth by backfilling with equivalent cap material and reseeding. Repairs are usually pursued in the spring or fall to enhance revegetation efforts. Due to the ongoing activity, repairs are required on a continuing basis.

No other deficiencies of the cover system or appurtenant structures, including drainage channels and access roads, were noted. With the exception of the rodent holes no intrusive activities were noted on the cover system and no landfill waste or other contaminants were exposed or appeared likely to be exposed. The leachate treatment system was found to be operating and functioning properly. All monitoring well covers are intact and locked and show no signs of damage. Ongoing activities are operating smoothly.

Interviews

The following individuals were contacted by telephone as part of the five-year review:

- · Rick Lanham, Illinois EPA Project Manager(Interviewed 1/24/03)
- · Donald Kulek, City Engineer, City of Quincy (Interviewed 11/21/03)
- Phil Harvey, Contractor for the City (Interviewed 1/23/03)

Mr. Kulek stated that there are no serious issues related to the site. He noted that groundwater use restrictions remain in place. He also stated that community interest about the site remains low. The area residents seem to be confident that the water they receive through the municipal supply is safe. Mr. Kulek confirmed that no changes in land use were planned for the site, and confirmed that deed restrictions and institutional controls are in place at the site.

VII. TECHNICAL ASSESSMENT

Question A: Is the remedy functioning as intended by the decision documents?

The review of documents, applicable or relevant and appropriate requirements (ARARs), risk assumptions, and the results of the site inspection indicates that the remedy is functioning as intended by the ROD, as modified by the ESDs. Citizens are on public water supply and a leachate collection system is in place, these two factors have achieved the remedial objectives to minimize the migration of contaminants to groundwater and surface water and prevent direct

contact with, or ingestion of, contaminants in soils and sediments.

- *HASP/Contingency Plan:* Both the HASP and the Contingency Plan are in place, sufficient to control risks, and properly implemented.
- Implementation of Institutional Controls and Other Measures: The City needs to provide security services for the site to prevent further trespassing and erosion. The fence needs to be maintained. Institutional controls are in place and no current or planned changes in land use at the site suggest that they are not effective.
- Remedial Action Performance: The landfill cover system has been effective in isolating waste and contaminants.

 As previously discussed, some minor erosion/rutting has occurred on the cap but it does not affect the performance or integrity of the cover system. There is no evidence of wetland deterioration due to the site. These factors indicate that the remedial actions continue to be effective and operating and functioning as designed.
- · System Operations/O&M: System operations procedures are mostly consistent with requirements.
- · Cost of System Operations/O&M: Costs for the most part have been within an acceptable range.
- *Opportunities for Optimization:* Given the adequate performance at the site, this five-year review does not identify a need for optimization at this time.
- Early Indicators of Potential Remedy Failure: No early indicators of potential remedy failure were noted during the review.

Question B: Are the exposure assumptions, toxicity data, cleanup levels, and remedial action objectives (RAOs) used at the time of the remedy selection still valid?

There have been no changes in the physical conditions of the Adams County/Quincy Landfill site that would affect the protectiveness of the remedy.

Changes in Standards and To be Considers

As the remedial work has been completed, most ARARs for sediment, soil and debris contamination cited in the ROD have been met. There have been no changes in these ARARs and no new standards or to be considers (TBCs) affecting the protectiveness of the remedy.

Changes in Exposure Pathways, Toxicity, and Other Contaminant Characteristics

There have been no changes in the toxicity factors for the contaminants of concern that were used in the baseline risk assessment. These assumptions are considered to be conservative and reasonable in evaluating risk and developing risk-based cleanup levels. No change to these assumptions, or the cleanup levels developed from them is warranted. There has been no change to the standardized risk assessment methodology that could affect the protectiveness of the remedy. The remedy is progressing as expected and it is expected that all groundwater cleanup levels will be met within 30 years, as specified in the ROD.

Question C: Has any other information come to light that could call into question the protectiveness of the remedy?

No other events have affected the protectiveness of the remedy and there is no other information that calls into question the short term and long term protectiveness of the remedy.

Technical Assessment Summary

According to the data reviewed and the site inspections, the remedy is functioning as intended by the ROD. There have been no changes in the physical conditions of the site that would affect the protectiveness of the remedy. ARARs for soil, groundwater and sediment contamination cited in the ROD have been met. There have been no changes in the toxicity factors for the contaminants of concern that were used in the baseline risk assessment, and there have been no changes to the standardized risk assessment methodology that could affect the protectiveness of the remedy. There is no other information available that calls into question the protectiveness of the remedy.

VIII. ISSUES

The primary operation performed at the site is the removal of leachate from the leachate storage tank and transport it to an off-site treatment facility. Possible problems associated with the operation include: access difficulties, driving accidents, leachate spills, and administrative concerns.

Access difficulties can be addressed by ensuring that the personnel engaged to perform the leachate removal operation coordinate their arrival in advance with the appropriate Group representative, currently anticipated being the City of Quincy. This will allow the City of Quincy to secure the site access road for the tanker truck arrival. It will also allow the City of Quincy an opportunity to coordinate activities at the site if other personnel are scheduled to be on site at the same time. The leachate removal personnel should be provided with a map of the site and have access to a two-way radio in case of access problems or emergencies.

Driving accidents can be avoided through proper access road maintenance and a reduced speed on the part of the driver. Vehicles should not exceed 15 miles per hour on the site access road. Drivers must concentrate at the task-at-hand and be unimpaired by the influence of alcohol or drugs.

Leachate spills can be avoided if proper procedures are followed during the transfer of leachate from the storage tank to the tanker. Connections must be secure and maintained until the flow of leachate is complete and the risk line spillage is no longer present. The tanker should be equipped with spill containment materials in the event a spill occurs. Spill containment materials, If used, must be disposed of properly in accordance with applicable regulations.

Administrative concerns such as coordination of disposal schedules and leachate management operations should be reviewed on a continual basis. The City of Quincy must assume and maintain responsibility for items of this type to ensure administrative problems do not occur.

Table 10 - Issues

Issue	Currently Affects Protectiveness (Y/N)	Affects Future Protectiveness (Y/N)
Signs of Trespassing	N	Y
Minor damage to cover	N	Y
Maintenance of monitoring wells	N	Y
Security Measures required	N	Y

IX. Recommendations and Follow-Up Actions

Table 11 - Recommendations and Follow-Up Actions

Issue	Recommendati ons/ Follow-up actions	Party Responsible	Oversight Agency	Milestone Date	Affects Protectiveness? (Y/N)	
					Current	Future
Trespassing	Continue to monitor the site and post signs where trespassing is most likely to occur.	City of Quincy	Illinois EPA	Spring 2003	N	Y
Damage to landfill cover	Keep heavy equipment off of the cover and repair eroded areas as they occur.	City of Quincy	Illinois EPA	Summer 2003	Z	Y
Monitoring wells require maintenance	Replace rusted locks and cracked covers.	City of Quincy	Illinois EPA	Summer 2003	N	Y
Security Measures	Repair fence where needed and put up more warning signs where trespassing is likely to occur.	City of Quincy	Illinois EPA	Until cleanup goals are met	N	Y

It is recommended that inspections should be also be performed after extreme meteorological events, such as tornados or extreme rainfall, to ensure the integrity of the access road or cap has not been comprised. The site fencing, gates, and the existing storage building will be inspected at the same frequency as the cover system at least 3-4 times a year. Repairs should be performed when determined through Inspection.

The passive landfill gas management system consists of vent pipes located throughout the area of final cover system installation. These vents will be inspected at the same frequency and duration as the cover system.

X. Protectiveness Statement

The remedy is protective of human health and the environment in the short term. There are no current exposure pathways and the remedy appears to be functioning as designed. The cover and putting citizens on public water supply eliminates the source of contamination and have achieved the remedial objectives to minimize the migration of contaminants to groundwater and surface water and prevent direct contact with, or ingestion of, contaminants in soils and sediments.


The cap is effective at containing contaminants through preventing infiltration of rainwater and preventing direct contact with contaminated soils. There is no evidence of wetland degradation. Institutional controls at the landfill remain in place and are effective. Gaps in the fence at the site have been repaired and additional warning signs will be in place in early spring to reduce trespassing.

Long-term protectiveness of the of the remedial action will be achieved when cleanup goals are met.

XI. Next Review

The next five-year review for the Adams County/Quincy Landfill site is required by March 2008, five years from the date of this review.

ATTACHMENTS



ATTACHMENT 2

List of Documents Reviewed

- · Emergency Response Action Report
- · Final Remedial Investigation and Feasibility Study:
- · CERCLA Record of Decision
- · Final Remedial Design Report:
- · Final Close-Out Report:
- · Annual Operation and Maintenance Report,

ATTACHMENT 3

Attachment 3

OSWER No. 9355.7-03B-P

Please note that "O&M" is referred to throughout this checklist At sites where Long Term Response Actions are in progress, O&M activities may be referred to as "system operations" since these sites are not considered to be in the O&M phase while being remediated under the Superfund program.

Five-Year Review Site Inspection Checklist (Template)

(Working document for site inspection. Information may be completed by hand and attached to the Five-Year Review report as supporting documentation of site status. "N/A" refers to "not applicable.")

I. SITE INF	ORMATION
Site name: Muni 2/3 Alans Gutty Landen	Date of inspection: June 2002 - Date Afr 2002
Location and Region: Quacy Illinons Respons	EPA ID: ILN 480607055
Agency, office, or company leading the five-year review: U.S. Eff (Eston V, Hege, IL	Weather/temperature:
Remedy Includes: (Check all that apply) Landfill cover/containment Access controls	Monitored natural attenuation Groundwater containment Vertical barrier walls
Attachments:	☐ Site map attached
II. INTERVIEWS	(Check all that apply)
1. O&M site manager Donaho J. Kunek Name Interviewed Dat site Dat office M by phone Phone Problems, suggestions; [] Report attached	ne no.211.220.4530
2. O&M staff Red. Davis Name Interviewed [] at site [] at office [] by phone Phone Problems, suggestions: [] Report attached	ne no.117. 228.4534
Local regulatory authorities and response age office, police department, office of public healt	encies (i.e., State and Tribal offices, emergency response th or environmental health, zoning office, recorder of

Agency IEPA			
Contact Rick Lawham			
Name	Title	Date	Phone no.
Problems; suggestions; Report attached			
Agency TERRY Round TREE USER	A	_	
Contact	REVERIAL PROJECTICLE	1 Markon	S12-353-32
Name	Title	Date	Phone no.
Problems; suggestions; Report attached			
Agency			
Contact			
Name	Title	Date	Phone no.
Problems; suggestions; ☐ Report attached _	1. 14.		
Agency			
Contact Name			
Name Problems: suggestions; ☐ Report attached		Date	Phone no.
Other interviews (optional) Report attach	ned.		
III. ON-SITE DOCUMENTS & RE	CORDS VERIFIED	(Check all that app	oly)
O&M Documents			
	□ Readily available	E-Up to date	□ N/A
As-built drawings	Readily available	D Up to date	□ N/A

	☐ Maintenance logs Remarks	□ Readily available	□ Up to date	NA
	Site-Specific Health and Safety Plan Contingency plan/emergency response p Remarks	Readily available		□ N/A □ N/A
	O&M and OSHA Training Records Remarks		Up to date	□ N/A
	Permits and Service Agreements Air discharge permit Effluent discharge Waste disposal, POTW Other permits Remarks		Up to date	© N/A N/A N/A N/A
	Gas Generation Records	dily available Up to	o date X N/A	\
-	Settlement Monument Records Remarks BENCH MARK ON S	図Readily available		□ N/A
	Groundwater Monitoring Records Remarks	Readily available	Up to date	□ N/A
	Leachate Extraction Records Remarks SACHAT EXTRACTION	Readily available 16 A GRAVITY		
	Discharge Compliance Records ☐ Air ☐ Water (effluent) Remarks MANJEESTS & LAB RE	□ Readily available Readily available SAATS FOR COL	□ Up to date □ Up to date トモCTE の 人	ØN/A □N/A EBCHOTE
	Daily Access/Security Logs Remarks	☐ Readily available	□ Up to date	№ N/A
	IV.	O&M COSTS		
	O&M Organization			*

	e in-house		☐ Contractor for State						
•	in-house	_	☐ Contractor for PRP						
	eral Facility	in-house	☐ Contractor for Feder	al Facility					
☐ Oth	er								
	Cost Record								
	dily availabl								
		ism/agreement							
Origina	al O&M cost	estimate		eakdown anached					
		Total annual c	ost by year for review po	eriod if available					
From F	1-1999	ToB-1000	\$ 154.194 54	☐ Breakdown attached					
_	Date	Date	Total cost	Breakdown attached Available					
From £	-2000	TO B-2001	\$ 201,153,36	Breakdown attached					
	Date	Date	Total cost						
From £		To A-1002	123,923.86	Breakdown attached					
	Date	Date	Total cost						
From 9	-2002	LO LBEREUL		Breakdown attached					
From	Date	Date r_	Total cost						
From_	Date	ToDate	Total cost	☐ Breakdown attached					
	Jac	Date	i otal cost						
3. Unant Descri	cipated or be costs and	Unusually High	O&M Costs During R	teview Period					
A. Fencing	V. ACCE	SS AND INSTI	TUTIONAL CONTRO	OLS MApplicable IN/A					
l. Fencin Remark	g damaged Ks	□ Loca	tion shown on site map	☐ Gates secured ☐	□ N/A				
B. Other Acce	ss Restriction	១៣៩							
1. Signs a Remar		curity measure SIGN &	es 🗆 Location sh TN PLACE	lown on site map					
C. Institutiona	l Controls (ICs)							
I. lmpler	nentation a	nd enforcemen	<u></u>						

	Site conditions imply ICs not properly implemented Site conditions imply ICs not being fully enforced	☐ Yes No ☐ N/A ☐ Yes No ☐ N/A
	Type of monitoring (e.g., self-reporting, drive by) Datue B. Frequency Datue By's Twice Weekly / Wal Responsible party/agency Rog Davis	K & WALK SITE K SITE MONTHLY
	CONTROL RAD DAYTO ENG TECH	1. 111 128 4634
	Name Tide	Date Phone no.
	Reporting is up-to-date	□ Yes □ No XN/A
	Reports are verified by the lead agency	□ Yes □ No ■ N/A
	Specific requirements in deed or decision documents have be	en met X Yes DNo DN/A
	Violations have been reported	☐ Yes ☐ No DONA
	Other problems or suggestions: STIE IS STILL GWNED BY THE CT	TY OF QUENCY, A PRP
2.	Adequacy ICs are adequate IICs a	
D. G :	eneral Vandalism/trespassing Location shown on site map	No vandalism avident
	Remarks tresposing has occurred in the past	Walled validatistit cylidett
2.	Land use changes on site N/A Remarks	
3.	Land use changes off site N/A Remarks	
	VI. GENERAL SITE CONDIT	TONS
A. R	oads 💆 Applicable 🗆 N/A	
1	Roads damaged M Location shown on site map Remarks ACCESS ROAD TO LEACHATE CON ALEDED DURING WINTER MONTHS	Roads adequate N/A
B. O	ther Site Conditions	
	Remarks	

OSWER No. 9355.7-03B-P VII. LANDFILL COVERS Applicable IN/A A. Landfill Surface Settlement (Low spots) ١. ☐ Location shown on site map ☐ Settlement not evident Areal extent Depth_ Remarks SETTLEMENT OF TOPSOIL STARTING TO SHOW BEHIND BERMS. WILL SURVEY & DETERMINE EXTENT FILL & RESEED 2. Cracking not evident Cracks ☐ Location shown on site map Widths _____ Depths__ Lengths__ Remarks 3. Erosion ☐ Location shown on site map Erosion not evident Areal extent____ Hales not evident ☐ Location shown on site map Areal extent_____ Depth____ Remarks 5. M Grass Vegetative Cover ☐ Trees/Shrubs (indicate size and locations on a diagram) Remarks X N/A Alternative Cover (armored rock, concrete, etc.) Remarks _____ 7. ☐ Location shown on site map Bulges not evident Bulges Areal extent_____ Height____ Remarks____ 8. Wet Areas/Water Damage ☐ Wet areas/water damage not evident ☐ Wct arcas ☐ Location shown on site map Areal extent Ponding Seeps ☐ Location shown on site map Areal extent ☐ Location shown on site map Areal extent ☐ Soft subgrade ☐ Location shown on site map Areal extent_

	Remarks PONDING	th Settle Areas !	SEWND BERMS
9.	Slope Instability Areal extent Remarks		map No evidence of slope instability
В. В	(Horizontally constructed	plicable [] N/A If mounds of earth placed across a st e velocity of surface runoff and inte	eep landfill side slope to interrupt the slope respt and convey the runoff to a lined
I.	Flows Bypass Bench Remarks	□ Location shown on sit	e map 🕱 N/A or okay
2.		☐ Location shown on site map	N/A or okay
3.	Bench Overtopped Remarks	☐ Location shown on si	e map N/A or okay
C. L	ctdown Channels App (Channel lined with eros side slope of the cover an landfill cover without cre	ion control mats, riprap, grout bags, nd will allow the runoff water collect	or gabions that descend down the steep ted by the benches to move off of the
1.	Areal extent	☐ Location shown on site map Depth	No evidence of settlement
2.	Material Degradation Material type Remarks	☐ Location shown on site map Areal extent	_
3.	Erosion Areal extent Remarks	CI Location shown on site map Depth	No evidence of erosion
4.	Undercutting Areal extent Remarks	☐ Location shown on site map Depth	No evidence of undercutting
5.	Obstructions Type		No obstructions

	□ Location shown on site map Areal extent Size Remarks
6.	Excessive Vegetative Growth Type GREE & SORRINGS No evidence of excessive growth Vegetation in channels does not obstruct flow Location shown on site map Areal extent Remarks + 1 INCH DIA. COTTONWOOD SAPPLINGS ARE SUBMING UP IN RYP RAP CHANNELS. WILL BE CAT THIS SORING.
D. Cov	r Penetrations (Applicable N/A
1.	Gas Vents
2.	Gas Monitoring Probes ∴ Properly secured/locked □ Functioning □ Routinely sampled □ Good condition □ Evidence of leakage at penetration □ Needs Maintenance ☑ N/A Remarks
3.	Monitoring Wells (within surface area of landfill) A Properly secured/locked A Functioning □ Routinely sampled ■ Good condition □ Evidence of leakage at penetration □ Needs Maintenance □ N/A Remarks Well ○ 1 ○ To BE REPAIRED BEFORE NEXT SAMPLING EVENT WELL BENT QURING MOWING
4	Leachate Extraction Wells A Properly secured/locked Functioning Needs Maintenance N/A Remark FC HATE EXTRACTION PL 15 10E UST THAT LEACHATE COLLECTION SYSTEM DRAINS TO.
5.	Settlement Monuments Located Routinely surveyed MN/A Remarks BENCUMARK ON STIE
E. Gas	Collection and Treatment Applicable X N/A
l	Gas Treatment Facilities ☐ Flaring ☐ Thermal destruction ☐ Collection for reuse ☐ Good condition ☐ Needs Maintenance Remarks

2.	Gas Collection Wells, M Good condition Remarks	anifolds and Piping Deeds Maintenance	
3.	☐ Good condition Remarks <u>Cas Montro</u> R	S (e.g., gas monitoring of adjacent Needs Maintenance N/ IM6 Pt-5 UNRER NEGOTE EAGEMENT FOR AFF STE	
F.	Cover Drainage Layer	☐ Applicable	□ N/A
1.	Outlet Pipes Inspected Remarks	☐ Functioning	□ N/A
2.	Outlet Rock Inspected Remarks	☐ Functioning	□ N/A
G.	Detention/Sedimentation Pon	ds 🗆 Applicable	X N/A
	Siltation Areal extent Siltation not evident Remarks	Depth	
2.	☐ Erosion not evident	stentDepth	
3.	Outlet Works Remarks	☐ Functioning ☐ N/A	
4.	Dam Remarks	☐ Functioning ☐ N/A	
Н.	Retaining Walls	☐ Applicable N/A	
1.	Deformations Horizontal displacement Rotational displacement Remarks	CI Location shown on site map Vertical displace	
2	Degradation Remarks	[] Location shown on site map	☐ Degradation not evident

L. Pe	rimeter Ditches/Off-Site I	Discharge Applicable N/A
1.	Areal extent	cation shown on site map X Siltation not evident Depth
2.	Vegetation does not Areal extent Remarks	☐ Location shown on site map ☐ N/A impede flow Type
3.	Erosion Areal extent	☐ Location shown on site map
4.	Discharge Structure Remarks	Functioning N/A
	VIII. VE	RTICAL BARRIER WALLS Applicable N/A
1.	Settlement Areal extent Remarks	☐ Location shown on site map ☐ Settlement not evident ☐ Depth ☐
2.	☐ Performance not mo Frequency Head differential	ing Type of monitoring
-	IX. GROUNDWA	TER/SURFACE WATER REMEDIES
A. (Vells, Pumps, and Pipelines ☐ Applicable ☐ N/A
i .	Pumps, Wellhead Plu	
2.	☐ Good condition Remarks	pelines, Valves, Valve Boxes, and Other Appurtenances □ Needs Maintenance

3.	Spare Parts and Equi M Readily available Remarks	☐ Good condition	• • -	ade 🖺 Need	ds to be provided
B. St	arface Water Collection S	itructures, Pumps,	and Pipelines 🗆 .	Applicable	N/A
1.	Collection Structures. Good condition Remarks	, Pumps, and Electr ☐ Needs Mainte	ENANCE		
2.	Surface Water Collect Good condition Remarks	tion System Pipelin Needs Mainte		es, and Othe	r Appurtenances
3.	Spare Parts and Equi Readily available Remarks	☐ Good condition		rade 🗆 Need	ds to be provided
C. T	reatment System	☐ Applicable	X N/A		
1.	☐ Additive (e.g., chela	☐ Oil/o ☐ Carb ation agent, flocculer ☐ Nece perly marked and fun nce log displayed and identified	water separation poin adsorbers at) ds Maintenance actional d up to date		emediation
	☐ Quantity of surface Remarks	water treated annual	ly		
2.	Damada	and Panels (properl	☐ Needs Maintenand	5	
3.	Tanks, Vaults, Storag	ge Vessels ood condition	☐ Proper secondary	containment	□ Needs Maintenance

4_	Discharge Structure and Appurtenances N/A Good condition Needs Maintenance Remarks
5.	Treatment Building(s) N/A
6.	Monitoring Wells (pump and treatment remedy) ☐ Properly secured/locked ☐ Functioning ☐ Routinely sampled ☐ Good condition ☐ All required wells located ☐ Needs Maintenance ☐ N/A Remarks
D. M	onitoring Data
•	Monitoring Data ☐ Is routinely submitted on time Is of acceptable quality
•	Monitoring data suggests: ☐ Groundwater plume is effectively contained declining ☐ Contaminant concentrations are
D. M	Ionitored Natural Attenuation
1.	Monitoring Wells (natural attenuation remedy) □ Properly secured/locked □ Variationing □ Routinely sampled □ All required wells located □ Needs Maintenance □ N/A Remarks
	X. OTHER REMEDIES
	If there are remedies applied at the site which are not covered above, attach an inspection sheet describing the physical nature and condition of any facility associated with the remedy. An example would be soil vapor extraction.
	XI. OVERALL OBSERVATIONS
A.	Implementation of the Remedy
	Describe issues and observations relating to whether the remedy is effective and functioning as designed. Begin with a brief statement of what the remedy is to accomplish (i.e., to contain contaminant plume, minimize infiltration and gas emission, etc.).

OSWER No. 9355.7-03B-P B. Adequacy of O&M Describe issues and observations related to the implementation and scope of O&M procedures. In particular, discuss their relationship to the current and long-term protectiveness of the remedy. the remedy is responding effectively in the short-term and stould be just as effective in the loopy form if O'm activity continues. C. Early Indicators of Potential Remedy Problems Describe issues and observations such as unexpected changes in the cost or scope of O&M or a high frequency of unscheduled repairs, that suggest that the protectiveness of the remedy may be compromised in the future. Minor Cover Vepirs, & Posting of the No tresposing Signs D. Opportunities for Optimization Describe possible opportunities for optimization in monitoring tasks or the operation of the remedy. SHE IS IN its early Stayes of OGH to Early for Optimization Opportunities

ATTACHMENT 4

SUMARY OF GROUNDWATER CHEMICAL DATA -SHALLOW WELLS ADAMS COUNTY QUINCY LANDFILLS 2 AND 3 QUINCY, ILLINOIS

	, ·-	m = 1,2 m		~	1 20	20	20	211	[2tr]	žu	zii	i žu: i	31)	3D	340	31)	30
		Class :	21)	21)	20 9123/97	213 1/14/98	11/12/00	3/27/97	7/1/97	9/24/97	1/15/98	12/13/00	3/25/97	7/1/97	9/23/97	1/14/98	11/13/00
		Remediation	3/26/97	6/30/97	37.1314/	1/14/76	LATRZAUB	302/13/	/11/3/	5129192	17 1.3V.7IP	* to socialn	OT 2.1137	ATAIS?	JELJIN	11 12 17 17 17	***************************************
		Objectives					A som T			1						1	2 54 2 8
Parameters	Units	75		12 1	-		App. I					1		 	 	}	
1,4-Dichlorobeuzene	дв/1.				9.6							·					
4-cidoro-3-methylphenal	14871.				100		 					 -				t · · · ·	
Acetophenoire	RB/1	28006		47 13						:						·	· · · · · · · · · · · · · · · · · · ·
Benzoic Acid	pg/L			24		14 B	ļ	11			4.3 JB	ļ	21	 	9.5 JB	8 10	d
Bis(2-ethyllusyl)phthalate	ρg/1.	ь	6.1 3 15	9.8	ļ .	19 19]		3 14.	 		 	1.5		1 *
Diethyl Phihalate	pg/L	5600		11	ŀ	ļ 	 							f	f	f · · · -	
Dissethyl Phthalate	ρg/[.			11	120	5.8 T	 								 		St. 1. St. 1930
Di N-hutyl Phthalate	pg/1.		;		720	17	J			}:				 -		i	
Hexactilorophene	μg/(.		34 J							ļ		-	<u> </u>	 -		f	
Prenol	1/34	1981		Ī		ļ	ł ———								· · · · · · · · · · · · · · · · · · ·	 	++
OCDD	bh	1	Ì		#:4B		}	1	<u> </u>	ļ-· ·- · ·			}		-	· · · · · · · · · · · · · · · · · · ·	10000
Cyanide	mg/L	0,	1		0.051		1					 	· · ·			 	
Aluminum, Dissolved	mg/L	.	1	0.1 t			0.59						·	 	ļ	ł	
Alemanus, Total	11871				ļ		8.37	 	 				1			ļ	
Antimony, Dissolved	nig/!	0.00/	ĺ		·	ļ									-		
Antimony, Total	mig/L	6.00x-	-		0.000	0.07								0.002	0.004	0.004	
Arsenic, Dissolved	areg/1.	0.05	0.11	0.1	0.089	0.07	· · · · · · · · ·	+			0.006		0 0 08	0.002	0.004	0.005	
Arsenic, Total	mg/1.	0.95	0.12	0.11		0.17	1.9		ļ		0.000		G CAND	0.025	17-4(50)	0.00.5	
Barium, Dissolved	ing/l.	?	0.81	1.3	1.3	f	1	4	ļ	ļ				 			
Barkon, Total	nig/1.	. ?	ã.92	1.3	17	0.96	2.5	4		ļ		·		 -	 	 	<u> </u>
Cadanium, Dissolved	nig/L	0.00	1	4					L		ļ		ļ	 			J
Cadmiuso, Fotal	nig/l.	0.000					000	ļ	ļ		ļ	<u> </u>		ļ			4
Calcium, Dissolved	nig/l.		170	210	2.30	170	278	 					ļ	<u> </u>		 	منے سے ا
Calcium, Total	nig/L			1			291	.				1			 		1
Chromium, Dissolved	DIG/1	4 0 ±		in the second		22.5		1	-			ļ		 _	. -	ļ	
Chromium, Lotal	mg/l.	0-1		1	1	0.002		!		ļ		 	ļ <u></u>	 	ļ		1
Cabalt, Dissolved	mg/L		0.0%	0.029	ļ	0 907		1		ļ							<u> </u>
Coball, Total	mg/l.	#	0.017	n n.29	111)35	0.013				ļ	L	L	+			 	
Copper, Dissolved	mg/f.	0.6"			1			İ			ļ			ļ	ļ	-	السنسيد ا
Copper, Total	11/8/11	0.65	1	ļ <u></u>		0.016	ļ, <u>.</u>		ļ						ļ	ļ	
Iron, Dissolved (Ferric)	mg/L	15	31	390	34	29		1					ļ		<u> </u>		
tion, Dissolved	mg/L	5					20.5	0.035	0.963	0.063			5.5	7.5	6.3	6.8	11.0
Iron, Total	nig/L	5				1	27.9	0.34	0.43	0.72	0.85		7.7	16	7.1	9.3	8.9
l ead, Dissolved	mg/L	0.0075			0.012			J	l		1						
Lead, Total	mg/l.	0.0075		0 003	0.017	0.006	1		[[1	
Magnesium, Dissalved	mg/t.	1	7:	98	79	75	136	1	1	1	1						1
Magnesium, Total	mg/1.	1	1			j	156		1	1					<u></u>		
Manganese, Dissolved	mg/l.	0 15	48	2.7	2.7	2	2.4]		0.021	0.005		1.1	1.1	ORG	88.0	14
Manganese, Total	mg/l.	0.15				1	1.6	0.024	0.046	0.14	0.15	1	1.1	1.2	T	0.92	1.3
Mercury, Total	mg/t.	o aci		į	-	1		7		T		1			1	1	T
Nickel, Thissolved	ing/L	01	0.014	0.062	1055	0.03.1	0.10	1	T	†	1	[1	 	T
Nickel, Total	ing/l.	a.i	0.034	U.866	1.075	0.038	8.11	1	† -					1	1 -		
Polassium, Dissolved	nig/L	1	1.7	2	23	2 8	5.6	4	†	1							+
Potassium, Total			\		1		7.6	-	+	 			1			f	1
Selenium, Dissolved	org/1.	0.05					1	0.014	0018	0.026	0.015	-	'	-		† · · · · · ·	1
Scientian, Dissorved Scientian, Tutal	mg/l.	0.01	t	1	Ė	1		0.02	9 018	0.025	0.014	·	1	0.901	i :	1	1
Silver, Dissolved	118/1	605			3	1							-	1		-	
CHINES, LASSESTERS	1	1 7.0.			L	4	1	1	ı		1 _	1	1		.1	1	

SUMARY OF GROUNDWATER CHEMICAL DATA -SHALLOW WELLS ADAMS COUNTY QUINCY LANDFILLS 2 AND 3 QUINCY, ILLINOIS

	l	Class 1	2D	20	20	2 D	2.0	211	211	Zti	215	211	3D	3D	3D	30	31)
		Remediation	3/26/97	6/30/97	9/23/97	1/14/98	11/12/00	3/27/97	7fU97	9/24/97	1/15/98	11/13/00	3/25/97	711/97	9/23/97	1/14/98	11/13/00
	ł	Objective:)	Į	1							∮					1. X 14
aramelers	Units						App. I										
odinut, Dissylved	mg/L		270	34()	330	260	518										- X - V - X
odium, Total	mg/f.						621			ļ !]					. 4
ballium, Dissolved	mg/l	0.002			1					ļ		Land and					
Dalbium, Total	mg/L	₩.0 02		ļ		ا	1					l					
in, Dissolved	urg/L	1		0.466	9.06	0.056	ļ <u>. </u>										
in, Total	mg/L	1		0.089	0.071	0 .067											
inc, Dissolved	mg/l	5	0.016	0.056	0.011	ļ			0.069	0.04			0.017	0.14	0.091	0.04	
inc, Total	mg/L	5	0.024	0.013	0.089	0.938	ļ	O.ODA	0.27	0.075	0.005	İ	04025	9.48	0.11	9.91	
A-000 (p.p'4000)	48/1	0.11					l			l							
Milia	μg/1	0.04	tuen r			<u> </u>											
leta-BiHC	µg/1						0.067 S			l :			-				F 77 77
)elta-13) [[1189	1		}			I										
leptacklor	μ ₈ /1	04					1).
, t-Dichtoroethane	ng/1	70XI	16	31 1	31		1							1			-
A-Dioxane	11811	l		}		! !											
-Bulanone	#g/I						[22.1				,	
ketone	4g/1	70 0	6.R 18	L H J	14 (83 JR					4.7 (13					2.9 IB	7 7 3
returillie	#g/1.	(92 1]		4 1 1					
lenzeue	μg/1	5	7 1	49 1	45 1	1.8	6.4									·	
hlorobenzeur	μg/1.	100	2]	56	6.7	19 J	12										
hilomethane	μg/l.		4.8 £		13	71											
hloromethanc	ME/T	}		ŗ	5 (The State of the Control of the Cont]					
is-1,2-Dichteroethene	mg/	70	i = j								 						
Sectional Busingellane	ige/	1, 1	1.5 j										-			2.4	
strythenzene	96/	700	1.8	10	8.7	7.2	1 12	Ī]	1		t	!		. 		
sobulario	48/1.				1	_	1					† • · · · · · · · · · · · · · · · · · ·	f			†	1
Medinerytonitrile	#8/1 .			Ĩ	'21	Ī.	1	T		1					1		+
Methylene Chlaride	ME.	5	j			,		1	l	 -	_	 		 			
Toluçue	PB/	1000	0.2	1			1	1		1	T	•	1-	1		} ··· ·	J
caus 1,2 Dichloroethene	#X/5.	100							†					1	1		+ : :
richlomethone	mg/1.	5		İ			1	1	1		1						+
Varyl Chloride	pg/1.	2	Ì	1	1	T77 J	† : -	1		 		· i · · · · · · · · · · ·	1	 -	 		
kylenes, Total	μg/1.	1000	02 7	5.6	/ 63		3.8										

SUMARY OF GROUNDWATER CHEMICAL DATA -SHALLOW WELLS ADAMS COUNTY QUINCY LANDFILLS 2 AND 3 QUINCY, ILLINOIS

							QUIN	ICY, ILLIN	013									
		Class 1	40	40	(D)	40	40	40	Q45	Q4S	Q45	Q4S	Q48	Q5S	Q5S	Q5S	Q5S	Q5S
		Remediation	3/25/97	N/30/97	9/23/97	1/13/98	11/21/00	11/11/00	3/25/97	711197	9/23/97	1/14/98	11/12/00	3/26/97	7/1/97	9/23/97	1/14/98	11/11/00
		Objectives					1	Dap.								Ì		1.0 mm 44.
Parameters	Unuts						App. t	App.1		i		1	9	l				S * ·
1,4-Dichlozobenzene	μg/(.	75		1		1				1	T				† · · · · ·			1 7 7 7
4-chloro-3-methylphenol	μg/1.]	1	1				1					1	<u> </u>		
Acetophenone	μg/1.	1	1	1					1	1		1		i	 	† · · · · ·		· · · · · · · · · · · · · · · · · · ·
Benzolc Acid	μg/1.	28000	ĺ	9.1 JE	3	1				1			T		† ·	†	 	
Bis(2-ethylinexyl)philialate	μg/1.	6		8.1	1	16 B				27	7.6 JE	6.6		61	40	93	63 B	1 2 7
Dieflyd Phihalate	μg/1.	5600										 	- 94.00		 		<u></u>	
Dimethyl Philialate	μ g/l .			1 -	Ť					1			 		†			
Di-N-butyl Puthelate	pg/1.		.,	1	210						-		137		†	 		†****
I kwachturoptiene	µg/€.			1	1						 				ļ			
Phenol	P8/1.	100		t				-		 						 	 	
OCOU	ppt				1					 			—		<u> </u>			
Cyanide	mg/L	9.2	•	0.012	1					0.029	 							
Atominana, Dissolved	nig/I			T						 							 	
Aluminum, Total	ng/L			1									1		1	- · · · · · · · · · · · · · · · · · · ·	-	l***
Antimony, Dissolved	mg/L	Q.DXI6				0.024					-							
Antimory, Total	mg/t.	0.006		· · · ·	1	0.021	1			1	1							200
Arsenic, Dissulved	mg/L	0.05	0.0003		0.003	0.1304					0.003			0.002	0.001			
Arsenic, Total	ng/L	0.05	0.005	i	0.0 05	0.003				0.005	0.004	0.002		0.003	1	0.603		
Baritum, Dissolved	mg/L	2	0.11	0.11	0 081	0.14							† I	- 1177	 		 	
Parison, Total	mg/L		å 12	0.15	0.0423	0.13							1			 		
Cadmium, Dissolved	mg/I	0.00S			•	D+X01					 				·	 		C C
Cadmiuu, Total	mg/L	G.OH35			-	0.003				ļ			ļ			···	ļ ·	2
Calcium, Dissolved	nig/L		220	200	180	240	244	224			· · ·							
Calcium, Total	mg/L		at 1000			-	236	246		†								, / ×44
Chronium, Dissolved	ing/L	0.				0.002												7.1
Chromusus, Total	uig/L	a		601	1	0.011												 .
Cubalt, Dissolved	mg/L	i i				0.011					·							
Cobalt, Total	mg/L	ī i			-	0.01					i		 					بيث هندور
Copper, Dissolved	nig/L	065			1 "	0.IXI8							-		·			ئىنىدە <u>،</u>
Copper, Total	ng/L	0.65		0.022]	0.011										· · · · · · · · · · · · · · · · · · ·		بينون والمنافق
Iron, Dissolved (Ferric)	ang/L	ï	18	19	23					-		· · · · · · ·			-			بسد بجيدة أأم
Iron, Dissolved	mg/t.						23	22		0.067			l	0 23	0.099	0.091	0.78	المنظم بي الم
Iron, Total	neg/L	5			-		23	2.4	0.76	0л8	0.47	0 12	0.20	i i	1			36
Lead, Dissolved	ng/L	0.0075	0.003		0.054	0,003		÷				~ ~ ~			1	0.43	0.76	3.7
Lead, Total	mg/L	0.0025	0 004	0.014	0.054	0.01					 							۔ د جنے ا
	mg/L		71	63	60	77	29.5	724					1		 			
Afagnesium, Total	mg/L	··· +		- "			77	80.1					ļ ļ					د. رياسا م نس ساية «جم
Manganese, Dissolved	mg/L	0.15	A I	18	33	45	5.2	4.7	0.01				0.020	0.000				
Manganese, Total	118/1	O Li					5	5.2	D.079	0.00	0.026		L 1	0.019	0.071	0.01	0.01	U.36
Mercury, Total	ing/f	0.003				0.0003		3.7	U.977	0.064	0 0.5		0.024	0.053	0.028	0.02B	9.037	0,36
		0.1			-	0.021									<u></u>		I	
Nickel, Total	mg/L	-01	4]	L			
	ing/l.	0.0	1	13.43.		0.057			- ,							_ []	1	
Potassium, Dissolved	mg/l.		' S	0.98	0.69	14												
Intersian, rock	mq.21.					. '												
Seleatium, Discolved	ang/1	0.0%								ļ.,					0.002	-		1
Selections, Total	nig/1.	0.05			1 4e .					0.001]	-	0.003	0.001		Γ
Silver, Dissalved	nig/l	0.05								1								

SUMARY OF GROUNDWATER CHEMICAL DATA-SHALLOW WELLS ADAMS COUNTY QUINCY LANDFILLS 2 AND 3 QUINCY, ILLINOIS

~	I	Class 1		1 4D	T 4D	41)	40	NCY, ILLIN	Q45	Qus	QIS	Q45	E Que	0.55	Q55	QSS	QSS	T AFE
		Remediation	3/25/97	6/30/97	9/23/97	1/13/98	11/11/00	21/11/00	3/25/97	7/1/97	9/23/97	1/14/98	11/12/00	3/26/97	7/1/97	9/23/97	1/14/98	Q55 11/11/00
	1	Objectives	ł		1		1 1	Dup.		1	j]			
Parameters	Units				1		Арр. Т	App.I					14.4	ĺ		1	[
Sodium, Dissolved	ing/L	1	79	55	52	67	70.2	64.3					1.00			 	 	\$50,000,000,000,000
Sudjum, Total	ng/L	1		1			68	70.8		1								
Thallium, Dissolved	neg/l.	D. 002			1		17.	- 348g	· · · · · · · · · · · · · · · · · · ·	T-	1		1					
Thallieun, Total	mg/L	0.002		ľ	7					T								4
Tim, Dissolved	mg/L		0.056			0.069										T	†——	
Tin, Total	ing/L	1	6.075	0.057		D.06	2.00											1901 11 (1900 - No.
Zinc, Dissolved	rug/	5	6,033	0.025	0.055	0.026	0.026	0.020	0.015	0.086	0.009			0,029	0.028	0.099	† — — —	2 . W. A
Zive, Total	mg/L	5	0.042	0.098	0.067	0.055	0.020	0.021	0.023	2.4	0.16			0.028	0.15	0.099	0.066	· · · ·
4,4"-DDD (p,p"-DDD)	µg/1.	011		T	7		i Sign				7							
Ahlrin	д6/1.	0.04	1	0.01									7			İ	F	200
Beta-BCC	µg/1	1	1	1	1			T	j	T	1 1		1			1		7 10 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Della-BEIC	ME/L.	1		0.01	1						1					†	f	######################################
Heptachlor	Mg/1.	0.4		0.01	1						1						t	
1,1-Dichlororthane	µg/1	700	30	29	26	26	30	30			1 - 1		25			† · · · · · · · · · · · · · · · · · ·	!	77.
1,4-Dioxiuse	μg/1.									1		/				i .		27.00
2-Butanone	μg/1.	1]			12.8		1			1				2.7 I	10000
Acelone	µg/l.	700		3.1]				1.5 B		11	2.7 JU	1	0.8 10			22 TE	1 × × ×
Acetonitrile	μg/1.	1]					1	1		1 - 1					[
Benzene	μg/1.	5	0.5 1							1	I							
Chlorobenzene	μg/1.	1GC		1		-					1 - 1		1					
Cidoroethane	μg/1		71		8.9	84 1	6.6	6.9	-	1	1 1		1					1.5
Chloromethane	μg/1.	1			21			3			1 1		 -	·				100
Cis-1,2-Dichlorue thene	MB/I	70	15	15	11	12	16	16		1	1 1		14					3 3 3
Dichtorodiffuoromethme	P8/1				1	1.6 J				—	tt		1				·	
Ethylberzene	M8/1	7D9	*					15.46.		<u> </u>	tt		† †					بيور فحدثون
Isohe (ano)	μg/1.				- '					1	f		1					
Methacrylomitrile	ng/(**	1				1	1 1		1 1					
Methylere Chloride	1971	5						7 90	0.7 JB	1	† 		1			 	*** .	lyze (* 4
Tohwie	µg/f	1000			- 1				0.1 JB	<u> </u>	1 -		1.3					
Trace 1,2-Dichlorcethene	μg/I	100	0.7		" -					İ	† I		1				<u> </u>	
Trichlarne thene	д g/1	5			olyma				L	†	1 1		4.7					
Vinyl Chloride	pg/t	2	35	-	23 1	26	<2.0	2.0		<u> </u>	 		t +					
) i			d					4 . ~.	I		I					Probability of the

Vinyl Clubride Xylenes, Total

рв/I. Рв/I.

10000

SUMARY OF GROUNDWATER CHEMICAL DATA -SHALLOW WELLS ADAMS COUNTY QUINCY LANDFILLS 2 AND 3 QUINCY, ILLINOIS

		Class 1 Remediation Objectives	Q3D 3/25/97	Q3D 6/38/97	Q3D 9/23/97	Q3D 1/13/99	Q3D 11/11/00	Q4D 3/25/97	Q41) 6/3 0 /97	Q4D 9/23/97	Q4D 1/16/98	Q4D 11/13/00	Q\$D 11/13/00 Dap
Parameters	Units] '					Арр 1						
,4 Dichlosobenzene	μg/L	75		1		Ī							
-chloro-3-mellysphenol	μg/1.	1		1									
Acetophenone	μg/1 .	1				l							
lenzolc Acid	118/1	28000		1	<u> </u>	1							
Bis(2 ethylbexyl)phthalate	(ag/1	6	15	24	19	8.8			6.8				
Diethyl Phihabie	PB/1	5600											
June Byl Philialate	pg/1	1		1	1	[L			
)i-N-butyl Pluhalate	1184		,		290							1. 1. 1. 3	1 to 200
lexachtorophene	µg/I	† i		t	 								***
'henoi	μg/i	100		1								N. 2	
XIDD	p ₁ 4	∮				7							
'yanide	ang/l	0.2				1	 		0 0018				77.
Mundinum, Dissolved	mg/l	† ~~~			t	 		l				1	
Munimum, Total	ng/I	· · · · · · · · · · · · · · · · · · ·			t· · · ·	t	 					-	
Intimony, Dissolved	ing/i	6.006		J	}	0.009		† · · · · ·					Harris San Co
Antimony, Total	ung/	0.006				0.000	ale male and a						
Arsenic, Dissolved	mg/L	8.05	0.005		0.003			0 .005	0.004	0.003			
Arsenic, Total		1.05	0 006		0.007	0.001		0.005	0.005	0.006	0.021		
Arium, Dissolved	1/800	2	0.11	0.11	0.093	0.1101 0.111		17.11.03	- U.SIA)	0.000			
	mg/l	2	0.17	<u> </u>	0.11	0.12	-						
larium, Total	mg/l		0.17	0.12	U.11		<u> </u>						
admitten, Dissolved	μις/i.	0 005			ļ	0.001	<u> </u>	ļ				L	
admium, Total	1918/6	0 005			L	ļ		L					
alcium, Dissolver	mg/t		200	190	190	170	231		j ,				
alcium, Total	nig/)	l			ļ		232						
hromium, Dissolved	ing/i	9.1				0.001						12 2 3	
lwominu, Total	mg/	61				0.002		L					
inhalt, Dissolved	nig/	1	0.022	0.019	0.012	0.02							
'ohalt. Total	mg/i	1	0.023	0.019	0.015	0.023							
Capper, Dissolved	mg/L	0.65		1		800.0						1850/114	
apper, Total	mg/1.	0.65				1							
ron, Dissolved (Ferric)	mg/L.	.5	0.98	12	1.1	1]					
ron, Dissolved	mg/l	5			1		1.7	8.7	0.7	0.57	0.41	10	1.0
ron, Total	uig/i	5				1	1.7	0.79	1.4	0.65	3.8	1.0	1.3
ead, Dissolved	ing/1	0 007			0.034	0.001	7			1		1	
ead, Total	ung/1	0 0075		0.003	0.09	8.002						· · · · · · · · · · · · · · · · · · ·	
lagnesium, Dissolved	mg/i	1	48	45	#4	41	52.2						-
Jagnesium, Intai	1027			1]	52.4						
danganese, Dissolved	mg/L	0 .15	4.3	38	3.5	3.6	4.8	1.8	1.4	0.67	15	1.4	1.4
Sanganese, Total	mg/t.	0.15			<u> </u>	 	4.7	1.9	1.4	0.71	1.4	1.4	1.4
fercury, Total		0.002			 	 	200 2.6 00	 		0.71	1.1	13 - 13 - 1 - 1 - 13 - 13 - 1 - 1	10 YEAR
	ing/(11.1	Λ.Δ=2	0.047		0.05	0.061						L
lickel, Dissolved	mg/L	1	0.013		0.047	1							
lickel, Total	nig/L	n i	D.D.16	0 049	0.047	0.057	0.041						
otassituo, Dissolveti	mg/I	Į	2.7	13	1.8	1.8							
otassium, Total	arg/i			Į			·						
elenium, Dissolve I	mg/1.	0.05				1							
elenium, Total	mg/L	0.05				l			i]	
silver, Dissilved	nig/L	9.05			1	1	1	1			1	1	i -

TABLE Page 6 at 6

SUMARY OF GROUNDWATER CHEMICAL DATA-SHALLOW WELLS ADAMS COUNTY QUINCY LANDFILLS 2 AND 3

OHINCY	. 11	LIN	ZIOIS

		Class I Remediation Objectives	Q3D 3125/97	Q3D 6/30/97	Q3D 3/23/97	Q3D 1/13/98	Q3D 11/11/08	Q4D 3/25/97	Q4D 6f30f97	Q4D 9/23/97	(2412. 2/16/98	QAQ. 3 11/13/00	QAQ2. 11/13/00 Dup.
Parameters	Donis	1	1	1	\	<u>'</u>	App.1	1		l			9
Sodium, Dissolved	mg/L		57	16	42	38	49.8				Γ.	35	
Sodium, Total	mg/L						50						98.5
Thallium, Dissolved	ng/L	0.602			D.03				Γ	I			100
Thalliam, Total	mg/1	0.002			9.017	I				I			
Thi, Dissolved	mg/L	1	T										240
Tin, Total	112/f.			· · ·		0.055				l			
Zinc, Dissolved	mg/L	- 5	0.032	U.027	0.029	0.028	0.035	0.014	0.078	0.032	0.035	1	
Zinc, Total	nig/f.	5	0.035	0.051	0.14	0.021	0.035	0.045	0.13	0.056	D.028		
(,4'-000 (p,p'-000)	ME/(.	0.03		0.05 J					1		E		
Aldrin	mg/1.	0104									L		
Bela-BIIC	MR/L								F .				9.3
Delta-Bl K.	×g/1	1		0.01					Ī			,	
Lieptachlor	μg/1.	0.4		1									
1.1-Dichloroettane	pg/1	700	42.	47	35	40	37	19	12	47 3	*	3.8	3.7
1.4-Dioxane	μg/1.												
2-Bulanone	µg/1.	Ī		_							•	1. 7.	
Acetone	μg/1	700	1	,	4 1	<u> </u>				1			
Acetonitrile	μg/L									_			
Benzene	48/1	5	-		1	T	1			1	_		
Chlordrenzeuc	1 08/1	160	-		<u> </u>	1		-				1	
Chloroethane	pg/l	for the control of	74		8.7	12	6.9	3.4 J		1.5	33	2.6	23
Chloromethane	μg/1.		į.		1.5	İ		İ	l	l · · · · · · ·	1	1	
Cis-1,2-Dichloroethene	ng/L	70	1.5	18	11	13	15	4.3	1		7 4	1.5	1.4
Dicklarediffuoromethane	ug/I	j. – ·		1	·	T	1	1	1		•	1.,	
Ethylbenzene	MR/L	700	1		1	i —	1	1	l	1	_		
Isobatanoi	με/1.			·	1	Ī		85	-			-	
Methacrylometrile	mg/I	·			· · · · · ·	T -	T						
Methylene Chloride	rg/1.	1			I	1		I		_			
Tolueire	pg/1.	1000	0.2				1.7]	1	•		1	
Trans-1,2-Dichloroc shone	pg/1.	100		1					-		1		I
Trichlosoetheur	ng/I	5	1.9		1 1	1.3	₹1.5	j	T		1		Ī
Viryl (tiloride	P8/1.	7	49]	4.3 J	2.8	42]	3.0	1.6 J				1	-
Xvience, Total	pg/I	TOIXIO			 	 			†			· · · · · · · · · · · · · · · · · · ·	<u> </u>

Note

analyte was positively identified, below the practical quantitation limit; concentration is estimated

Southying surrogate results; estimated concentration

^{8 -} analyte detected in associated method htank.

3.0 - Concentration exceeds Tier 1 Remediation Objective for Class 1 grunnthvater
App. 1 - Sample analyzed for Illinois Appendix 1 list of parameters